



# Paged Ultra Form

(specialty formwork plywood panel design to last longer and serve during multiple uses)

Specialty formwork plywood panel design to last longer and serve during multiple uses thus saving it's users time and money. Its superb mechanical properties combined with hard-wear coating provides for an ideal solution. Paged Ultra Form is resistant to UV lightening and chemical agents. It is perfect for vertical, special and frame formwork systems.

### KEY BENEFITS AND APPLICATIONS

- Main applications include: concrete prefabrications, façade panel manufacturing, formworks
- Increased durability of the product compared to phenolic film
- High UV resistance
- High crack resistance
- Made from responsibly sourced wood in Poland

**STANDARD SIZES [mm]** 1250 x 2500  
1500 x 2500/ 3000/ 3300

\*Other sizes available upon request

### Dimensional deviation as per EN 315 and EN 324

Length / width	Deviation
< 1000 mm	± 1 mm
1000 – 2000 mm	± 2 mm
> 2000 mm	± 3 mm
According to norm	± 3,5 mm

### NOMINAL THICKNESS WITH STANDARD DEVIATION, NUMBER OF PLYS, DENSITY AS PER EN 315, EN 323, EN 324

Nominal thickness (mm)*	Number of plies (pcs) – coating included	Standard deviation (mm)	Weight (kg/m2)	Density avg. (kg/m3)
9	7	-0,7	+0,5	7
12	9	-0,8	+0,6	9,3
15	11	-0,9	+0,7	11,6
18	13	-0,9	+0,7	14
21	15	-1,0	+0,8	16,3
24	17	-1,1	+0,8	18,6
27	19	-1,8	+1,4	20,9
30	21	-1,9	+1,5	23,3

700-850\*\*

\*Other thickness available upon request  
\*\*As measured at 8-12% moisture content

### Straightness and squareness deviation as per EN 315 and EN 324

± 0,1% or ± 1mm/m

### COATING

Coating type	Polypropylene
Thickness	1,4 mm
Density	1,0-1,1 g/cm3
Taber Abraser	14500 (no. of cycles)
Colour	Dark grey

### RELEASE OF FORMALDEHYDE (EN 717-1)

E1  
The product also meets the limit ½ E1.

### BONDING QUALITY (EN 314-2)

Class 3

### MACHINING

CNC machining and drilling on request

### ADDITIONAL INFORMATION

1. General Terms of Sales available from [www.sklejkapaged.pl/en](http://www.sklejkapaged.pl/en)
2. Declaration of Performance available from [www.sklejkapaged.pl/en](http://www.sklejkapaged.pl/en)
3. Film-faced plywood in-house norms and standards available from [www.sklejkapaged.pl/en](http://www.sklejkapaged.pl/en)



Our product is made of renewable resource. Our products are characterized by low carbon footprint and are produced from certified wood, thus respecting the natural environment and the local community. The information contained in this document is intended as a guideline only and comes without warranty. We reserve the right to amend product specification sheets without notice.