

DECLARATION OF PERFORMANCE, No 2025/07/10-DoP-HW-003

1. Identification code of the product-type:

Non-structural hardwood plywood with insulation insert, coated or uncoated, 9-30 mm.

2. Intended uses:

For plywood with unprotected surfaces and/or edges as a non-structural element in accordance with EN 636-2.

For plywood with protected surfaces and edges as a non-structural element in accordance with EN 636-3.

3. Manufacturer

Paged Plywood S.A. ul. Kwiatowa 1 12-200 Pisz, Polska Paged Plywood S.A. ul. Mazurska 1 14-300 Morąg, Polska

5. System of AVCP:

AVCP system 4



7. Declared performance:

		Hardwood plywood with	insulatio	on insert	
Essential characteristics	End use condition		min. thicknes s (mm)	Performance	
				Class (ex. floorings)	Reaction to fire
Reaction to fire	without an air gap behind the wood- based panel		9	D-s2, d0	D _{fi} -s1
	with a closed or an open air gap not more than 22 mm behind the wood- based panel		9	D-s2, d2	÷
	with a closed air gap behind the wood-based panel		15	D-s2, d1	D _{fl} -s1
	with an open air gap behind the wood-based panel		18	D-s2, d0	D _{fl} -s1
		any	3	E	Efi
Essential characteristic	s		Performance		
Water vapour permeability		Wet cup μ - 110 Dry cup μ - 250			
Release of formaldehyde		Class E1			
Content of pentachlorophenol (PC	CP)		None		
Airborne sound insulation		NPD			
Sound absorption α		Range		α	
		250-500 Hz 0,10		0	
		1000-2000 Hz		0,30	
Thermal conductivity λ (W/(mK))		0,24			
Bonding quality		Class 3			
Biological durability		Use class 2			
Embedment strength	nent strength		NPD		
Air permeability	r permeability		NPD		
Racking resistance		NPD			
Mean density (kg/m³)			950-1050)	

Performance of this product, as identified above, is in conformity with the set declared performances and characteristics. This declaration of performance is issued in accordance with Regulation EU No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Morąg, POLAND, 10th July 2025

Itana Perkourta

PAGED Plywood S.A.

14-300 Morag, ul. Mazurska 1 tel. centr. 89 757 9501, Fax 89 757 9599 NIP 741-13-78-488 510445569