

DECLARATION OF PERFORMANCE, No 2025/07/10-DoP-HW-008

1. Identification code of the product-type:

Non-structural hardwood plywood Paged DesignPly, overlaid with HPL, 9-30 mm.

2. Intended uses:

For plywood with unprotected surfaces and/or edges as a non-structural element in accordance with EN 636-2.

For plywood with protected surfaces and edges as a non-structural element in accordance with EN 636-3.

3. Manufacturer

Paged Plywood S.A.
ul. Kwiatowa 1
12-200 Pisz, Polska

Paged Plywood S.A.
ul. Mazurska 1
14-300 Morąg, Polska

5. System of AVCP:

AVCP system 4

7. Declared performance:

Paged DesignPly					
Essential characteristics	End use condition	min. thickness (mm)	Performance		
Reaction to fire			Class (ex. floorings)	Reaction to fire	
		without an air gap behind the wood-based panel	9	D-s2, d0	D _{fl} -s1
		with a closed or an open air gap not more than 22 mm behind the wood-based panel	9	D-s2, d2	-
		with a closed air gap behind the wood-based panel	15	D-s2, d1	D _{fl} -s1
		with an open air gap behind the wood-based panel	18	D-s2, d0	D _{fl} -s1
	any	3	E	E _{fl}	
Essential characteristics		Performance			
Water vapour permeability		Wet cup μ - 92 Dry cup μ - 225			
Release of formaldehyde		Class E1			
Content of pentachlorophenol (PCP)		None			
Airborne sound insulation		NPD			
Sound absorption α	Range		α		
	250-500 Hz		0,10		
	1000-2000 Hz		0,30		
Thermal conductivity λ (W/(mK))		0,19			
Bonding quality		Class 3			
Biological durability	Uncoated or coated and unprotected		Use class 2		
	Coated with protected edges		Use class 3		
Embedment strength		NPD			
Air permeability		NPD			
Racking resistance		NPD			
Mean density (kg/m³)		720-820			

Harmonized standard EN 13986+A1:2015

Harmonized standard EN 13986+A1:2015

Performance of this product, as identified above, is in conformity with the set declared performances and characteristics. This declaration of performance is issued in accordance with Regulation EU No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Morąg, POLAND, 10th July 2025

Anna Perkowski

PAGED Plywood S.A.
14-300 Morąg, ul. Mazurska 1
tel. centr. 89 757 9501, Fax 89 757 9599
NIP 741-13-78-488
510445569