

DECLARATION OF PERFORMANCE, No 2025/07/10-DoP-SW-003

1. Identification code of the product-type:

Non-structural thick ply softwood plywood, coated or uncoated, 6-40 mm.

2. Intended uses:

For plywood with unprotected surfaces and/or edges as a non-structural element in accordance with EN 636-2.

For plywood with protected surfaces and edges as a non-structural element in accordance with EN 636-3.

3. Manufacturer

Paged Plywood S.A. ul. Mazurska 1 14-300 Morąg

5. System of AVCP:

AVCP system 4



Declared performance:

		Thick ply softwoo	d plywoo	d		
Essential characteristics		End use condition	min. thicknes	Performance		
Reaction to fire			s (mm)	Class (ex. floorings)	Reaction to fire	
	without an air gap behind the wood- based panel		9	D-s2, d0	D _{fl} -s1	
	with a closed or an open air gap not more than 22 mm behind the wood- based panel		9	D-s2, d2	-	
	with a closed air gap behind the wood-based panel		15	D-s2, d1	Dri-s1	
	with an open air gap behind the wood-based panel		18	D-s2, d0	D _{fl} -s1	_
		any	3	E	Eπ	2
Essential characteristics		Performance				2
Water vapour permeability		Wet cup μ - 70 Dry cup μ - 200				בת אום
Release of formaldehyde		Class E1				2
Content of pentachlorophenol (PCP)		None				
Airborne sound insulation		NPD				Halliolitzed stalldard EN 15360+A1.2013
Sound absorption α		Range		α		7.7
		250-500 Hz		0,10		Ę
		1000-2000 Hz		0,30		
Thermal conductivity λ (W/(mK))		0,11				
Bonding quality		Class 3				
Biological durability		Uncoated or coated and unprotected		Use class 2		
		Coated with protected edges		Use class 3		
Embedment strength		NPD				
Air permeability		NPD				
Racking resistance		NPD				
Mean density (kg/m³)			585			

Performance of this product, as identified above, is in conformity with the set declared performances and characteristics. This declaration of performance is issued in accordance with Regulation EU No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Morag, POLAND, 10th July 2025

Morio Perkowla

tel. centr. 89 757 9501, Fax 89 757 9599 NIP 741-13-78-488 510445569

PAGED Plywood S.A. 14-300 Morag, ul. Mazurska 1