

DECLARATION OF PERFORMANCE, No 2025/07/10-DoP-HW-004

1. **Identification code of the product-type:**
Non-structural hardwood plywood Paged GreenPly, coated or uncoated, 12-18 mm.
2. **Intended uses:**
For internal use as a non-structural component in dry conditions according to EN 636-1.
3. **Manufacturer**
Paged Plywood S.A.
ul. Kwiatowa 1
12-200 Pisz, Poland
5. **System of AVCP:**
AVCP system 4

7. Declared performance:

Hardwood plywood				
Essential characteristics	End use condition	min. thickness (mm)	Performance	
Reaction to fire			Class (ex. floorings)	Reaction to fire
	without an air gap behind the wood-based panel	9	D-s2, d0	D _{fl} -s1
	with a closed or an open air gap not more than 22 mm behind the wood-based panel	9	D-s2, d2	-
	with a closed air gap behind the wood-based panel	15	D-s2, d1	D _{fl} -s1
	with an open air gap behind the wood-based panel	18	D-s2, d0	D _{fl} -s1
	any	3	E	E _{fl}
Essential characteristics		Performance		
Water vapour permeability		Wet cup μ - 90 Dry cup μ - 220		
Release of formaldehyde		Class E1		
Content of pentachlorophenol (PCP)		None		
Airborne sound insulation		NPD		
Sound absorption α	Range	α		
	250-500 Hz	0,10		
	1000-2000 Hz	0,30		
Thermal conductivity λ (W/(mK))		0,17		
Bonding quality		Class 1		
Biological durability		Use class 1		
Embedment strength		NPD		
Air permeability		NPD		
Racking resistance		NPD		
Mean density (kg/m ³)		640-760		

Harmonized standard EN 13986+A1:2015

Performance of this product, as identified above, is in conformity with the set declared performances and characteristics. This declaration of performance is issued in accordance with Regulation EU No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Morąg, POLAND, 10th July 2025

Janina Perkowski

PAGED Plywood S.A.
14-300 Morąg, ul. Mazurska 1
tel. centr. 89 757 9501, Fax 89 757 9599
NIP 741-13-78-488
510445569